

CR Series CR系列



- Solid metal shell construction
- Threaded coupling & color coded ring option
- Cost effective for industrial grade application

- Key polarization and alternate position
- Gold plated & solder contact terminals
- UL certified

No. of contacts 接點數及電氣規格：

CR2 :	2, 3 (pins)	15A / 250V	CR4 :	7 (pins)	10A / 250V
	4, 5, 7	10A / 250V		12, 16	8A / 250V
	10, 12	5A / 250V		17, 20, 26	4A / 250V
CR3 :	2, 3 (pins)	20A / 250V	CR5 :	24 (pins)	8A / 250V
	4, 5	15A / 250V			
	10	10A / 250V			
	14, 16	5A / 250V			



Series 規格系列	CRxR Box Mounting (Square Flange) 方型面板座				CRxA Box Mounting (Round Flange w/Hex lock nut) 圓型面板座				CRxD Wall Mounting w/backshell (Square Flange) 方型面板座 (束線型)			
	Male (公)		Female (母)		Male (公)		Female (母)		Male (公)		Female (母)	
Connector Style 外型式樣												
Outer Dimension of Connector 外型尺寸												
	A	B	C	D	A	B	C	D	A	B	C	D
CR2	21.8	26.4	sq 22.9	sq 29.0	21.8	9.9	26.4	28.5	21.8	47.8	sq 22.9	sq 29.0
CR3	25.4	26.8	sq 26.2	sq 32.0	25.4	10.3	26.8	31.5	25.4	53.4	sq 26.2	sq 32.0
CR4	29.8	26.8	sq 30.0	sq 35.0	29.8	10.5	26.8	34.5	29.8	55.0	sq 30.0	sq 35.0
CR5	38.0	40.0	sq 34.9	sq 44.8	38.0	20.8	40.0	44.0	38.0	72.0	sq 34.9	sq 44.8

Series 規格系列	CRxF Wall Mounting w/backshell (Round Flange w/Hex lock nut) 圓型面板座 (束線型)				CRxP-10 Straight Plug w/bushing 套環型接線接頭 (夾線式)				CRxE-10 Cable Extender w/bushing 延長型接線接頭 (夾線式)			
	Male (公)		Female (母)		Male (公)		Female (母)		Male (公)		Female (母)	
Connector Style 外型式樣												
Outer Dimension of Connector 外型尺寸												
	A	B	C	D	A	B	C	D	A	B	C	D
CR2	21.8	48.7	13.0	28.5	16.0	50.0	8.5	25.5	21.8	48.7	8.5	21.8
CR3	25.4	53.4	13.4	31.5	20.5	53.0	9.8	30.0	25.4	53.4	9.8	25.8
CR4	29.8	55.0	17.0	34.5	24.5	56.0	12.5	33.8	29.8	55.0	12.5	29.8
CR5	38.0	72.0	19.0	44.0	32.7	70.0	16.5	43.0	38.0	72.0	16.5	37.8

