

CS Series cs系列









- Solid metal shell construction
- Threaded coupling hard dielectric inserts
- Cost effective for industrial grade application







- Front Key polarization
- Solder contact terminals
- UL certified

No. of contacts 接點數及電氣規格：

CS1: 2, 3, 4, 5, 6, 7, 8 (pins)	5A / 125V
CS2: 2, 3, 4 (pins)	5A / 125V
CS3: 2, 3, 4, 5, 6 (pins)	10A / 250V
CS4: 2, 3, 4, 5, 7, 8 (PINS)	15A / 250V



Series 規格系列	CSxA Box Mounting Round Flange w/Hex Lock Nut 圓型面板座				CSxR Box Mounting (Screw Flange) 圓型面板座				CSxP Straight Plug 套環型接線接頭 (夾線式)			
	Male (公)				Male (公)	Female (母)			Male (公)		Female (母)	
Connector Style 外型式樣												
Outer Dimension of Connector 外型尺寸												
	A	B	C	D	A	B	C	D	A	B	C	D
CS1	15.6	5.5	20.5	18.3	-	-	-	-	12.5	18.0	8.6	43.3
CS2	-	-	-	-	33.0	25.0	120	25.5	14.6	22.0	10.0	43.0
CS3	-	-	-	-	42.2	27.5	120	33.5	21.0	27.7	10.8	50.3
CS4	-	-	-	-	46.0	29.3	120	37.8	24.9	33.0	12.3	54.8

Series 規格系列	CSxP-20 Straight Plug (For flexible conduit) 套環型接線接頭 (浪管式)				CSxP-Bxx Straight Plug (w/plastic cable gland clamp) 套環型接線接頭 (迫緊束線式)				Male (公)		Female (母)	
	Male (公)		Female (母)		Male (公)		Female (母)		Male (公)		Female (母)	
Connector Style 外型式樣												
Outer Dimension of Connector 外型尺寸												
	A	B	C	D	A	B	C	D	A	B	C	D
CS1	-	-	-	-	-	-	-	-				
CS2	-	-	-	-	-	-	-	-				
CS3	21.1	27.7	11.3	60.0	21.1	27.7	12.0	84.1				
CS4	25.6	33.0	11.3	60.0	25.6	33.0	12.0	90.2				